

# WS 200

## SINGLE PHASE VACUUM

### FOR NON-COMBUSTIBLE DUST



## APPLICATION

WS 200 H for small quantity cleaning of electro-static Nylon 6 and Nylon 12 powders.

Effective cleaning with suitable anti-static accessories and hoses.

## FEATURES AND BENEFITS

### WS 200

- Compact size ZONE 22 Vacuum
- Air shock filter dedusting possible during operation
- Low noise level
- Power socket with automatic start/stop
- Consistently high volume flow rate
- Easy to transport
- Dust collection in filter bag for hazardous dust

## WEAR PARTS / CONSUMABLES

MAIN FILTER



H FILTER



DUST FILTER BAG



## TECHNICAL SPECIFICATION



### WS 200 H ZONE 22

<b>MODEL</b>	WS 200 BLACK
<b>HOUSING</b>	Conductive Plastic
<b>DUTY</b>	Intermittent
<b>POWER</b>	1.2 kW
<b>ELECTRICAL SPEC.</b>	1 x 230 V 50/60 Hz IP54
<b>ATEX ZONE</b>	Zone 22
<b>FILTER CLASS</b>	H
<b>FILTER TYPE</b>	Canal Filter
<b>MAX. VACUUM</b>	- 230 mBar
<b>MAX. AIRFLOW</b>	200 m³/h
<b>NOISE LEVEL</b>	<70 dB (A)
<b>MAX. CAPACITY</b>	16 L
<b>CONNECTION</b>	50 mm
<b>DIMENSION W X L X H</b>	425 x 425 x 800 mm
<b>WEIGHT</b>	35 Kg.

## ACCESSORIES

### Consist in package:


- Anti-static Hose PUR Black DN35mm \* 2.5 m
- Curved Hand Pipe DN35mm - Stainless Steel
- Hand Pipe - DN35 mm - Stainless Steel
- Floor Tool - DN35 mm - 360 mm wide - strip brush, brass wheel, conductive plastic, and metal body
- Conductive rubber nozzle, L200, DN35mm - chamfered DN20mm suction side
- Universal brush DN35, 120x45mm straight - perlon trimming
- Transition piece DN35mm x L130mm - stainless steel
- Synthetic dust insert bag for WS200 - pack of 10pcs

RUWAC ASIA LTD.

700/295 Moo 1, AMATA CITY CHONBURI,  
T. BANKAO, A. PANTHONG, CHONBURI 20160 THAILAND  
TEL: +66 2 1054081 FAX: +66 38 468835

E-mail: [info@ruwac-asia.com](mailto:info@ruwac-asia.com)

[www.ruwac-asia.com](http://www.ruwac-asia.com)



# WS 200

## SINGLE PHASE VACUUM

### PRODUCT DETAIL



RUWAC ASIA LTD.

700/295 Moo 1, AMATA CITY CHONBURI,  
T. BANKAO, A. PANTHONG, CHONBURI 20160 THAILAND  
TEL: +66 2 1054081 FAX: +66 38 468835

[www.ruwac-asia.com](http://www.ruwac-asia.com)

E-mail: [info@ruwac-asia.com](mailto:info@ruwac-asia.com)